More Than Spirobifluorene: Low-Cost, Stable and High-Performance Spiro[fluorene-9,9'-xanthene] Derivatives for Organic Electronics

Maoxuan Sun,^a Bao-Yi Ren,^{*,a} and Ling-Hai Xie^{*,b}

^a College of Science, Shenyang University of Chemical Technology, Shenyang, Liaoning 110142, China

^b Center for Molecular Systems and Organic Devices (CMSOD), Key Laboratory for Organic Electronics and Information Displays & Institute of Advanced Materials (IAM), Nanjing University of Posts & Telecommunications, Nanjing, Jiangsu 210023, China

Email: renbaoyi@syuct.edu.cn (B.-Y. R.), iamlhxie@njupt.edu.cn (L.-H. X.)

Abstract Spiro[fluorene-9,9'-xanthene] has received great attention due to its unique structure and possesses wide applications in the field of material chemistry. Herein, we highlighted low-cost, stable and high-performance spiro[fluorene-9,9'-xanthene] derivatives for organic electronics.

Keywords spirobifluorene, spiro[fluorene-9,9'-xanthene], organic electronics

Since the spiro[fluorene-9,9'-xanthene] (SFX) with halogen atom or alkoxy substituents was firstly reported via the occasionally one-pot method in 2006 by us,^[1] huge progress in SFX has been made in terms of not only synthesis, structure diversity,^[2] structure-property relationship, but also materials for organic light-emitting diodes (OLEDs), organic photovoltaic (OPVs), as well as perovskite solar cells (PSCs). SFX building blocks are becoming a central core structure to replace spirobifluorenes (SBF) in the field of organic optoelectronics by means of the low-cost synthesis, high-stability, multi-function and well-defined design principle as well as flexible tailoring, simultaneously.

In the past 15 years, we have persistently made our best effort to decode the structure-function relationship and to design electronic or optical materials (Figure 1). A series of inspiring results and applications had already been achieved, including hole-transport materials (HTMs) in PSCs,^[3] host and emission materials in OLEDs,^[4-6] charge storage materials in transistor memory,^[7] laser materials, as well as corresponding crystal engineering.^[8] The dumbbell-shaped emitter of 1,6-di(spiro[fluorene-9,9'-xanthene]-2-yl)pyrene (**DSFXPy**) with enlarged pyrene-pyrene distance of up to 10.4 Å was designed and synthesized for high-performance nondoped deep-blue OLEDs. The DSFXPy-based nondoped OLED shows a maximum current efficiency (CE) of 7.4 cd/A, external quantum efficiency (EQE) of 4.6% (at 260 cd/m²) and excellent Commission Internationale de l'Éclairage (CIE) coordinates (0.16, 0.15) (at 6500 cd/m²), surpassing most reported nondoped deep-blue OLEDs.^[4] The phosphorescent emitter constructed from SFX-based ligands, tris(2-(spiro[fluorene-9,9'-xanthene]-2-yl)pyridinato) iridium(III) (**fac-Ir(SFXpy)₃**), shows more superior electroluminescent performance than the commercial phosphor bis(4-phenylthienyl)[3,2-c]pyridinato-C2,N(acetylacetonato)iridium(III) (**PO-01**), due to the key roles of the SFX-ligands for suppressing aggregation and assisting charge-carrier injection/transport.^[5] When using diphenylphosphine oxide to substitute the 4'-position of SFX through a short-axis linkage strategy, the 4'-diphenylphosphinoylspiro[fluorene-9,9'-xanthene] molecule (**SFXSPO**) possesses asymmetric and rigid steric hindrance owing to the non-planar xanthene and oblique fluorene of SFX. Using

SFXSPO as the host of full-color thermally activated delayed fluorescence (TADF) OLEDs, the corresponding devices exhibit the record EQE of 22.5% and 19.1% for the yellow and white TADF devices, respectively, manifesting that **SFXSPO** is highly efficient, universal host for TADF OLEDs.^[6] Undoubtedly, 2,2',7,7'-tetrakis[*N,N*-di(4-methoxyphenyl)amino]-9,9'-spirobifluorene (spiro-OMeTAD) is the most successful HTM constructed with SBF. However, the PSCs utilizing SFX oligomer or *N*-aryl substituted compounds as HTM show competitive and even better power conversion efficiency (PCE) than spiro-OMeTAD-based devices. A systematic research revealed that the HOMO levels of the HTMs were manipulated when attaching triphenylamine (TPA) on the fluorene moiety of SFX, while the glass transition (*T_g*) was affected through changing TPA to the xanthene moiety; the PSC based on **HTM-FX'**, in which TPA units was arranged on the 2,3',6',7'-positions of SFX, exhibits a PCE as high as 20.8% (the PCE of controlled Spiro-OMeTAD-based device is 20.4%).^[9] These research results indicate that the frontier molecular orbits (FMOs) levels, thermostability, spectrum stability, and morphology stability of the SFX-based materials can be elaborately manipulated. Thus, the clear structure and performance advantages sheds light on the bright perspective that rationally popularizing SFX-like structures in the field of organic electronics, benefitting from their characteristics of binary spiro-conjugation and multiple reactive sites.

In fact, there are more than fifty papers with direct correlations to SFX in the last 5 years, published in high-level journals including *Nature Chemistry*, *ACS Nano*, *Organic Letters*, *ACS-Applied Material & interface*, *Angewandte Chemie International Edition*, *Advanced Materials*, *Energy & Environmental Science*, *Chem*, *Advanced Energy Materials*, *Journal of Material Chemistry A*, etc. Relative patents have been applied for the company such as LG Chem/Display and CMDL, Co. (e.g., CN 108218842A, WO2018221930A1, CN 112106217A). At the same time, the "one-pot" protocol was further expanded from previous Friedel-Crafts route into nucleophilic aromatic substitution reaction (S_NAr) or carbon-cationic-relay mechanism,^[10] by which the facile preparation of dispiroxanthene-indenofluorene and spiro-diazafluorenes can also be promoted (Figure 2).

Spiro[fluorene-9,9'-xanthene] (SFX) Based Emitters, Hosts, and HTMs

Figure 1 The progress of SFX-based materials for organic electronics.

Org. Lett. 2016, 18, 6220–6223. Carbon Cationic Relay

Org. Lett. 2016, 18, 384–387. Twofold S_NAr Reaction

Figure 2 Evolving methodology for the synthesis of new SFX-like compounds.

Until now, SFX and its derivatives have been commercially available and mass-product by some companies in China for the application of electroluminescent materials according to abovementioned patents (CN 108218842A, WO2018221930A1, CN 112106217A). Therefore, it may be the right time to develop SFX and its analogues from synthesis, application, to design principle when SFX has increasingly been recognized and accepted by academia and industry.

Acknowledgement

We express sincere gratitude to the Soft Science Research Plan of Yingkou City (No. 2020JH2/0100017).

Conflict of Interest

The authors declare no conflict of interest.

Copyright © 2021 Maoxuan Sun, Bao-Yi Ren, and Ling-Hai Xie. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (<http://creativecommons.org/licenses/by/4.0/>). The use, distribution or reproduction in other forums is permitted, provided the original author(s) or licensor are credited and that the original publication in this journal is cited, in accordance with accepted academic practice. No use, distribution or reproduction is permitted which does not comply with these terms.

References

- [1] Xie, L.-H.; Liu, F.; Tang, C.; Hou, X.-Y.; Hua, Y.-R.; Fan, Q.-L.; Huang, W. Unexpected one-pot method to synthesize

spiro[fluorene-9,9'-xanthene] building blocks for blue-light-emitting materials. *Org. Lett.* **2006**, *8*, 2787–2790.

- [2] Liu, F.; Xie, L.-H.; Tang, C.; Liang, J.; Chen, Q.-Q.; Peng, B.; Wei, W.; Cao, Y.; Huang, W. Facile synthesis of spirocyclic aromatic hydrocarbon derivatives based on o-halobiaryl route and domino reaction for deep-blue organic semiconductors. *Org. Lett.* **2009**, *11*, 3850–3853.
- [3] Liu, K.; Yao, Y. H.; Wang, J. Y.; Zhu, L. F.; Sun, M. L.; Ren, B. Y.; Xie, L. H.; Luo, Y. H.; Meng, Q. B.; Zhan, X. W. Spiro[fluorene-9,9'-xanthene]-based hole transporting materials for efficient perovskite solar cells with enhanced stability. *Mater. Chem. Front.* **2017**, *1*, 100–110.
- [4] Gu, J. F.; Xie, G.-H.; Zhang, L.; Chen, S.-F.; Lin, Z.-Q.; Zhang, Z.-S.; Zhao, J.-F.; Xie, L.-H.; Tang, C.; Zhao, Y.; Liu, S.-Y.; Huang, W. Dumbbell-shaped spirocyclic aromatic hydrocarbon to control intermolecular pi-pi stacking interaction for high-performance nondoped deep-blue organic light-emitting devices. *J. Phys. Chem. Lett.* **2010**, *1*, 2849–2853.
- [5] Ren, B.-Y.; Guo, R.-D.; Zhong, D.-K.; Ou, C.-J.; Xiong, G.; Zhao, X.-H.; Sun, Y.-G.; Jurow, M.; Kang, J.; Zhao, Y.; Li, S.-B.; You, L.-X.; Wang, L.-W.; Liu, Y.; Huang, W. A yellow-emitting homoleptic iridium(III) complex constructed from a multifunctional spiro ligand for highly efficient phosphorescent organic light-emitting diodes. *Inorg. Chem.* **2017**, *56*, 8397–8407.
- [6] Li, J.; Ding, D. X.; Tao, Y. T.; Wei, Y.; Chen, R. F.; Xie, L. H.; Huang, W.; Xu, H. A significantly twisted spirocyclic phosphine oxide as a universal host for high-efficiency full-color thermally activated delayed fluorescence diodes. *Adv. Mater.* **2016**, *28*, 3122–3130.
- [7] Lin, Z.-Q.; Liang, J.; Sun, P.-J.; Liu, F.; Tay, Y.-Y.; Yi, M.-D.; Peng, K.; Xia, X.-H.; Xie, L.-H.; Zhou, X.-H.; Zhao, J.-F.; Huang, W. Spirocyclic aromatic hydrocarbon-based organic nanosheets for eco-friendly aqueous processed thin-film non-volatile memory devices. *Adv. Mater.* **2013**, *25*, 3664–3669.
- [8] Lin, Z.-Q.; Sun, P.-J.; Tay, Y.-Y.; et al. Kinetically controlled assembly of a spirocyclic aromatic hydrocarbon into polyhedral micro/nanocrystals. *ACS Nano* **2012**, *6*, 5309–5319.
- [9] Chiykowski, V. A.; Cao, Y.; Tan, H. R.; Tabor, D. P.; Sargent, E. H.; Aspuru-Guzik, A.; Berlinguette, C. P. Precise control of thermal and redox properties of organic hole-transport materials. *Angew. Chem. Int. Ed.* **2018**, *57*, 15529–15533.
- [10] Lin, D. Q.; Wei, Y.; Ou, C. J.; Huang, H.; Xie, L. H.; Tang, L.; Huang, W. Carbon cationic relay via superelectrophiles: Synthesis of spiro-diazafluorenes. *Org. Lett.* **2016**, *18*, 6220–6223.

Received January 18, 2021

Accepted October 12, 2021